

## CHILE

**169U-004 S1 ESD SRC**

Standard EN ISO 20345:2011

Sizes 36 - 47

Three-dimensional Spyder-net lining: high performance tight-knit three-dimensional structure textile gives an exceptional comfort and keeps the feet dry.

Double density polyurethane sole  
Tyre Pu-Pu SRC designed to offer maximum flexibility and lightness.



X-Weave high tenacity breathable nylon with differentiated zones. Extremely flexible, breathable, resistant to tearing and abrasion.

Easy-Fit system for perfect comfort.



**SRC** Slip resistant



**A** Antistatic



Resistant to 200 joules



**E** Energy Absorption of seat region



**FO** Fuel oil resistant sole

Maximum lightness and flexibility with Smart Injection, special moulding technology to obtain the Esolight compound, with high abrasion resistance. This process allows to get an exceptionally lighter and thinner outsole, thus giving an excellent flexibility.



PZ88 Fiberglass toe cap (200 Joule) provides high mechanical performances in a lightweight component conform to EN 20345 standards.



### Outsole TYRE PU/PU

- SRC Slip resistant outsole.
- Cleated profile for highest grip to the ground.
- FO Fuel resistance.
- Maximum lightness and flexibility thanks to the use of Smart Injection.
- Excellent abrasion resistance.

### Tyre · T-01

- Anatomic footbed for improved comfort.
- Diversified zones with cushioning effect.
- Conductive lining to reduce foam wearing.
- High density foam = Support and shock absorption.

