

PYTHON

269U-003 S3 SRC

Standard EN ISO 20345:2011

Sizes: 35-49

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Two-component sole Tyre Pu-Tpu designed to offer maximum flexibility and wear resistance. Thanks to the thermoplastic polyurethane, the outsole ensures outstanding mechanical characteristics while maintaining lightness and resistance to abrasion.



Two-Component sole TYRE PU-TPU

- TPU outsole= maximum flexibility, resistance and lightness
- SRC Slip-resistant outsole
- Hydrocarbon resistant
- Excellent abrasion resistance



Soft lycra collar.



Polyester fabric engineered to offer maximum

breathability and lightness guaranteeing water

dynamic look that makes the product unique in

repellency. All this provides a colourful and

combining aesthetics and functionality.





Antistaticity



Impact and compression resistance



Hydrocarbon resistant outsole



Puncture resistance



Energy absorption at the heel



Upper resistance to water penetration and absorption

X-Leather leather upper material reinforced with polyurethane multi-layer, high abrasion resistant.

Alu200 aluminium toe cap and Txzero puncture-proof insert made of multilayer textile for exceptional lightness, protection and flexibility.





Esolight 1.0 polyurethane midsole with jogging toe. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.

B-01 / Bubble

- Anti-fatigue polyurethane insole with dispersion of TPE spheres
- Maximum support
- Perforated for air circulation
- Lined with abrasion resistant fabric